

**METHOD AND SYSTEM FOR RESTRICTING AND ENHANCING TOPOLOGY
DISPLAYS FOR MULTI-CUSTOMER LOGICAL NETWORKS
WITHIN A NETWORK MANAGEMENT SYSTEM**

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an improved data processing system and, in particular, to a method and system for multiple computer or process coordinating. Still more particularly, the present invention provides a method and system for network management.

2. Description of Related Art

Technology expenditures have become a significant portion of operating costs for most enterprises, and businesses are constantly seeking ways to reduce information technology (IT) costs. This has given rise to an increasing number of outsourcing service providers, each promising, often contractually, to deliver reliable service while offloading the costly burdens of staffing, procuring, and maintaining an IT organization. While most service providers started as network pipe providers, they are moving into server outsourcing, application hosting, and desktop management. For those enterprises that do not outsource, they are demanding more accountability from their IT organizations as well as demanding that IT is integrated into their business goals. In both cases, "service level agreements" have been employed to contractually guarantee service delivery between an IT organization and its customers. As a result, IT teams now require management solutions that focus on and support "business processes" and

"service delivery" rather than just disk space monitoring and network pings.

IT solutions now require end-to-end management that includes network connectivity, server maintenance, and application management in order to succeed. The focus of IT organizations has turned to ensuring overall service delivery and not just the "towers" of network, server, desktop, and application. Management systems must fulfill two broad goals: a flexible approach that allows rapid deployment and configuration of new services for the customer; and an ability to support rapid delivery of the management tools themselves. A successful management solution fits into a heterogeneous environment, provides openness with which it can knit together management tools and other types of applications, and a consistent approach to managing all of the IT assets.

With all of these requirements, a successful management approach will also require attention to the needs of the staff within the IT organization to accomplish these goals: the ability of an IT team to deploy an appropriate set of management tasks to match the delegated responsibilities of the IT staff; the ability of an IT team to navigate the relationships and effects of all of their technology assets, including networks, middleware, and applications; the ability of an IT team to define their roles and responsibilities consistently and securely across the various management tasks; the ability of an IT team to define groups of customers and their services consistently across the various management tasks; and the ability of an IT team to address, partition, and reach consistently the managed devices.

Many service providers have stated the need to be able to scale their capabilities to manage millions of devices.

When one considers the number of customers in a home consumer network as well as pervasive devices, such as smart mobile phones, these numbers are quickly realized.

Significant bottlenecks appear when typical IT solutions attempt to support more than several thousand devices.

Given such network spaces, a management system must be very resistant to failure so that service attributes, such as response time, uptime, and throughput, are delivered in accordance with guarantees in a service level agreement. In addition, a service provider may attempt to support many customers within a single network management system. The service provider's profit margins may materialize from the ability to bill usage of a common management system to multiple customers.

On the other hand, the service provider must be able to support contractual agreements on an individual basis. Service attributes, such as response time, uptime, and throughput, must be determinable for each customer. In order to do so, a network management system must provide a suite of network management tools that is able to perform device monitoring and discovery for each customer's network while integrating these abilities across a shared network backbone to gather the network management information into the service provider's distributed data processing system. There is a direct relationship between the ability of a management system to provide network monitoring and discovery functionality and the ability of a service provider using the management system to serve multiple customers using a single management system. Preferably, the management system can replicate services, detect faults within a service, restart services, and reassign work to a replicated service. By implementing a common set of interfaces across all of their services, each service

developer gains the benefits of system robustness. A well-designed, component-oriented, highly distributed system can easily accept a variety of services on a common infrastructure with built-in fault-tolerance and levels of service.

Distributed data processing systems with thousands of nodes are known in the prior art. The nodes can be geographically dispersed, and the overall computing environment can be managed in a distributed manner. The managed environment can be logically separated into a series of loosely connected managed regions, each with its management server for managing local resources. The management servers coordinate activities across the enterprise and permit remote site management and operation. Local resources within one region can be exported for the use of other regions in a variety of manners.

As with most organizations, an IT organization, such as a service provider, may classify its personnel into different managerial roles. Given a scenario in which a service provider is using an integrated network management system for multiple customers, it is most likely that many different individuals will be assigned to manage different customers, different regions, and different groups of devices. In addition, separate individuals may have different duties within similar portions of the network, such as deploying new devices versus monitoring the uptime of those devices, and the management system should be able to differentiate the roles of the individuals and to restrict the actions of any particular individual to those operations that are appropriate for the individual's role. In a highly distributed system comprising on the order of a million devices, the task of authenticating and authorizing the actions of many individuals per customer, per region,

per device, etc., becomes quite complex.

In this type of environment, it would be valuable for an administrative user to be able to view management-related information through a variety of graphical user interfaces.

5 Typically, a network management application displays information associated with the physical configurations of a set of networks, such as information pertaining to the status and type of devices or communication links within the distributed system; various types of icons or color-coding
10 might be used to graphically differentiate the information so that an administrative user can view portions of networks in an easy-to-understand, graphical manner. However, for large distributed systems of more than a million devices, typical application displays would be filled with similar
15 icons for most subnetworks, which would be rather monotonous for an administrative user, and most displays would also appear to be redundant. Even though a user might be able to display device identifiers concurrently with graphical icons in order to distinguish different devices and systems, the
20 identifiers may also be similar to each other. In a highly distributed system with many customers and administrators using a common network management framework, graphical variations with respect to network-related information would be inadequate.

25 Moreover, it would be very valuable in a highly distributed environment for an administrative user to be able to request various presentation formats for the system's topology information within a graphical user interface. Typically, a network management application
30 allows an administrative user to zoom a user perspective with respect to a graphical layout of a set of networks; as the user zooms in or out, more or less detail within the networks is displayed. In a highly distributed system with

many customers and administrators using a common network management framework, varying the topology presentation format only with respect to levels of detail would be inadequate.

- 5 Therefore, it would be particularly advantageous to provide a method and system within a network management framework for displaying multi-customer information in a variety of presentation formats. It would be particularly advantageous for the network management system to provide an
- 10 ability to view non-network-related information in conjunction with the presentation of the topology of a network.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2

SUMMARY OF THE INVENTION

A method, system, apparatus, and computer program product are presented for management of a distributed data processing system on behalf of a plurality of management customers. A set of logical networks within the distributed data processing system and/or a set of physical networks in the distributed data processing system are associated with an anchor object. A topology map can be generated and displayed in which a root node of the topology map is the anchor object. Each anchor object is uniquely associated with a customer for which the distributed data processing system is managed. The topology display can be restricted such that portions of topology information are displayed to an administrative user in accordance with the authorized security access of the user.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, further objectives, and advantages thereof, will be best understood by reference to the following detailed description when read in conjunction with
10 the accompanying drawings, wherein:

Figure 1 is a diagram depicting a known logical configuration of software and hardware resources;

Figure 2A is simplified diagram illustrating a large distributed computing enterprise environment in which the
15 present invention is implemented;

Figure 2B is a block diagram of a preferred system management framework illustrating how the framework functionality is distributed across the gateway and its endpoints within a managed region;

20 **Figure 2C** is a block diagram of the elements that comprise the low cost framework (LCF) client component of the system management framework;

Figure 2D is a diagram depicting a logical configuration of software objects residing within a hardware
25 network similar to that shown in **Figure 2A**;

Figure 2E is a diagram depicting the logical relationships between components within a system management framework that includes two endpoints and a gateway;

30 **Figure 2F** is a diagram depicting the logical relationships between components within a system management framework that includes a gateway supporting two DKS-enabled applications;

Figure 2G is a diagram depicting the logical relationships between components within a system management framework that includes two gateways supporting two endpoints;

5 **Figure 3** is a block diagram depicting components within the system management framework that provide resource leasing management functionality within a distributed computing environment such as that shown in **Figures 2D-2E**;

10 **Figure 4** is a block diagram showing data stored by a the IPOP (IP Object Persistence) service;

Figure 5A is a block diagram showing the IPOP service in more detail;

Figure 5B is a network diagram depicting a set of routers that undergo a scoping process;

15 **Figure 5C** depicts the IP Object Security Hierarchy;

Figure 6 is a block diagram depicting a set of components that may be used to implement scope-based security access;

20 **Figure 7A** is a flowchart depicting a portion of an initialization process in which a network management system prepares a security subsystem for user access to network-related objects;

25 **Figure 7B** is a flowchart depicting further detail of the initialization process in which the DSC objects are initially created and stored;

Figure 7C is a flowchart depicting further detail of the initial DSC object creation process in which DSC objects are created and stored for an endpoint/user combination;

30 **Figure 7D** is a flowchart depicting further detail of the initial DSC object creation process in which DSC objects are created and stored for an endpoint/endpoint combination;

Figure 8A is a flowchart depicting a process for

creating topology data;

Figure 8B is a flowchart depicting a process for listening for physical network changes that affect topology objects;

5 **Figure 9A** is a figure depicting a graphical user interface window that may be used by a network or system administrator to view the topology of a network that is being monitored;

10 **Figure 9B** is a graphical user interface window that shows the topology of a network that has changed;

Figure 10A is a block diagram depicting a known configuration of software and/or hardware network components linking multiple networks;

15 **Figure 10B** is a block diagram depicting a service provider connected to two customers that each have subnets that may contain duplicate network addresses;

20 **Figure 11A** is a block diagram showing a set of components that may be used to implement multi-customer management across multiple networks in which duplicate address may be present;

Figures 11B-11D are some simplified pseudo-code examples that depict an object-oriented manner in which action objects and endpoint objects can be implemented;

25 **Figure 12A** is a flowchart depicting a portion of an initialization process in which a network management system prepares for managing a set of networks with multiple NATs;

Figure 12B is a flowchart depicting further detail of the initialization process in which the administrator resolves addressability problems;

30 **Figure 12C** is a flowchart depicting further detail of the process in which the administrator assigns VPN IDs;

Figure 13 is a figure that depicts a graphical user

interface (GUI) that may be used by a network or system administrator to set monitoring parameters for resolving address collisions;

Figure 14A is a flowchart showing the overall process for performing an IP "Ping" within a multi-customer, distributed data processing system containing multiple private networks; and

Figure 14B is a flowchart that depicts a process by which an administrator chooses the source endpoint and target endpoint for the IP "Ping" action described in an overall manner in **Figure 14A**;

Figure 15 is a flowchart depicting a process in which a newly discovered endpoint can be added to a multi-customer topology;

Figures 16A-16D are flowcharts depicting a process in which the network management framework can create different types of multi-customer topology views for an administrative GUI application using the anchor container objects of the present invention; and

Figure 17 is a flowchart depicting a process in which a display of a topology tree can be enhanced with non-network-related information

DETAILED DESCRIPTION OF THE INVENTION

5 The present invention provides a methodology for managing a distributed data processing system. The manner in which the system management is performed is described further below in more detail after the description of the preferred embodiment of the distributed computing
10 environment in which the present invention operates.

 With reference now to **Figure 1**, a diagram depicts a known logical configuration of software and hardware resources. In this example, the software is organized in an object-oriented system. Application object **102**, device
15 driver object **104**, and operating system object **106** communicate across network **108** with other objects and with hardware resources **110-114**.

 In general, the objects require some type of processing, input/output, or storage capability from the hardware resources. The objects may execute on the same
20 device to which the hardware resource is connected, or the objects may be physically dispersed throughout a distributed computing environment. The objects request access to the hardware resource in a variety of manners, e.g. operating
25 system calls to device drivers. Hardware resources are generally available on a first-come, first-serve basis in conjunction with some type of arbitration scheme to ensure that the requests for resources are fairly handled. In some
30 cases, priority may be given to certain requesters, but in most implementations, all requests are eventually processed.

 With reference now to **Figure 2A**, the present invention is preferably implemented in a large distributed computer

environment **210** comprising up to thousands of "nodes". The nodes will typically be geographically dispersed and the overall environment is "managed" in a distributed manner. Preferably, the managed environment is logically broken down into a series of loosely connected managed regions (MRs) **212**, each with its own management server **214** for managing local resources with the managed region. The network typically will include other servers (not shown) for carrying out other distributed network functions. These include name servers, security servers, file servers, thread servers, time servers and the like. Multiple servers **214** coordinate activities across the enterprise and permit remote management and operation. Each server **214** serves a number of gateway machines **216**, each of which in turn support a plurality of endpoints/terminal nodes **218**. The server **214** coordinates all activity within the managed region using a terminal node manager at server **214**.

With reference now to **Figure 2B**, each gateway machine **216** runs a server component **222** of a system management framework. The server component **222** is a multi-threaded runtime process that comprises several components: an object request broker (ORB) **221**, an authorization service **223**, object location service **225** and basic object adapter (BOA) **227**. Server component **222** also includes an object library **229**. Preferably, ORB **221** runs continuously, separate from the operating system, and it communicates with both server and client processes through separate stubs and skeletons via an interprocess communication (IPC) facility **219**. In particular, a secure remote procedure call (RPC) is used to invoke operations on remote objects. Gateway machine **216** also includes operating system **215** and thread mechanism **217**.

The system management framework, also termed

distributed kernel services (DKS), includes a client component **224** supported on each of the endpoint machines **218**. The client component **224** is a low cost, low maintenance application suite that is preferably "dataless" in the sense that system management data is not cached or stored there in a persistent manner. Implementation of the management framework in this "client-server" manner has significant advantages over the prior art, and it facilitates the connectivity of personal computers into the managed environment. It should be noted, however, that an endpoint may also have an ORB for remote object-oriented operations within the distributed environment, as explained in more detail further below.

Using an object-oriented approach, the system management framework facilitates execution of system management tasks required to manage the resources in the managed region. Such tasks are quite varied and include, without limitation, file and data distribution, network usage monitoring, user management, printer or other resource configuration management, and the like. In a preferred implementation, the object-oriented framework includes a Java runtime environment for well-known advantages, such as platform independence and standardized interfaces. Both gateways and endpoints operate portions of the system management tasks through cooperation between the client and server portions of the distributed kernel services.

In a large enterprise, such as the system that is illustrated in **Figure 2A**, there is preferably one server per managed region with some number of gateways. For a workgroup-size installation, e.g., a local area network, a single server-class machine may be used as both a server and a gateway. References herein to a distinct server and one

or more gateway(s) should thus not be taken by way of limitation as these elements may be combined into a single platform. For intermediate size installations, the managed region grows breadth-wise, with additional gateways then
5 being used to balance the load of the endpoints.

The server is the top-level authority over all gateways and endpoints. The server maintains an endpoint list, which keeps track of every endpoint in a managed region. This list preferably contains all information necessary to
10 uniquely identify and manage endpoints including, without limitation, such information as name, location, and machine type. The server also maintains the mapping between endpoints and gateways, and this mapping is preferably dynamic.

As noted above, there are one or more gateways per managed region. Preferably, a gateway is a fully managed node that has been configured to operate as a gateway. In certain circumstances, though, a gateway may be regarded as an endpoint. A gateway always has a network interface card (NIC), so a gateway is also always an endpoint. A gateway
20 usually uses itself as the first seed during a discovery process. Initially, a gateway does not have any information about endpoints. As endpoints login, the gateway builds an endpoint list for its endpoints. The gateway's duties preferably include: listening for endpoint login requests,
25 listening for endpoint update requests, and (its main task) acting as a gateway for method invocations on endpoints.

As also discussed above, the endpoint is a machine running the system management framework client component,
30 which is referred to herein as a management agent. The management agent has two main parts as illustrated in **Figure 2C**: daemon **226** and application runtime library **228**. Daemon

226 is responsible for endpoint login and for spawning application endpoint executables. Once an executable is spawned, daemon **226** has no further interaction with it. Each executable is linked with application runtime library **228**, which handles all further communication with the gateway.

Each endpoint is also a computing device. In one preferred embodiment of the invention, most of the endpoints are personal computers, e.g., desktop machines or laptops. In this architecture, the endpoints need not be high powered or complex machines or workstations. An endpoint computer preferably includes a Web browser such as Netscape Navigator or Microsoft Internet Explorer. An endpoint computer thus may be connected to a gateway via the Internet, an intranet, or some other computer network.

Preferably, the client-class framework running on each endpoint is a low-maintenance, low-cost framework that is ready to do management tasks but consumes few machine resources because it is normally in an idle state. Each endpoint may be "dataless" in the sense that system management data is not stored therein before or after a particular system management task is implemented or carried out.

With reference now to **Figure 2D**, a diagram depicts a logical configuration of software objects residing within a hardware network similar to that shown in **Figure 2A**. The endpoints in **Figure 2D** are similar to the endpoints shown in **Figure 2B**. Object-oriented software, similar to the collection of objects shown in **Figure 1**, executes on the endpoints. Endpoints **230** and **231** support application action object **232** and application object **233**, device driver objects **234-235**, and operating system objects **236-237** that

communicate across a network with other objects and hardware resources.

Resources can be grouped together by an enterprise into managed regions representing meaningful groups. Overlaid on these regions are domains that divide resources into groups of resources that are managed by gateways. The gateway machines provide access to the resources and also perform routine operations on the resources, such as polling.

Figure 2D shows that endpoints and objects can be grouped into managed regions that represent branch offices **238** and **239** of an enterprise, and certain resources are controlled by central office **240**. Neither a branch office nor a central office is necessarily restricted to a single physical location, but each represents some of the hardware resources of the distributed application framework, such as routers, system management servers, endpoints, gateways, and critical applications, such as corporate management Web servers. Different types of gateways can allow access to different types of resources, although a single gateway can serve as a portal to resources of different types.

With reference now to **Figure 2E**, a diagram depicts the logical relationships between components within a system management framework that includes two endpoints and a gateway. **Figure 2E** shows more detail of the relationship between components at an endpoint. Network **250** includes gateway **251** and endpoints **252** and **253**, which contain similar components, as indicated by the similar reference numerals used in the figure. An endpoint may support a set of applications **254** that use services provided by the distributed kernel services **255**, which may rely upon a set of platform-specific operating system resources **256**. Operating system resources may include TCP/IP-type

resources, SNMP-type resources, and other types of resources. For example, a subset of TCP/IP-type resources may be a line printer (LPR) resource that allows an endpoint to receive print jobs from other endpoints. Applications
5 **254** may also provide self-defined sets of resources that are accessible to other endpoints. Network device drivers **257** send and receive data through NIC hardware **258** to support communication at the endpoint.

With reference now to **Figure 2F**, a diagram depicts the
10 logical relationships between components within a system management framework that includes a gateway supporting two DKS-enabled applications. Gateway **260** communicates with network **262** through NIC **264**. Gateway **260** contains ORB **266** that supports DKS-enabled applications **268** and **269**. **Figure**
15 **2F** shows that a gateway can also support applications. In other words, a gateway should not be viewed as merely being a management platform but may also execute other types of applications.

With reference now to **Figure 2G**, a diagram depicts the
20 logical relationships between components within a system management framework that includes two gateways supporting two endpoints. Gateway **270** communicates with network **272** through NIC **274**. Gateway **270** contains ORB **276** that may provide a variety of services, as is explained in more
25 detail further below. In this particular example, **Figure 2G** shows that a gateway does not necessarily connect with individual endpoints.

Gateway **270** communicates through NIC **278** and network
279 with gateway **280** and its NIC **282**. Gateway **280** contains
30 ORB **284** for supporting a set of services. Gateway **280** communicates through NIC **286** and network **287** to endpoint **290** through its NIC **292** and to endpoint **294** through its NIC **296**.

Endpoint **290** contains ORB **298** while endpoint **294** does not contain an ORB. In this particular example, **Figure 2G** also shows that an endpoint does not necessarily contain an ORB. Hence, any use of endpoint **294** as a resource is performed
5 solely through management processes at gateway **280**.

Figures 2F and **2G** also depict the importance of gateways in determining routes/data paths within a highly distributed system for addressing resources within the system and for performing the actual routing of requests for
10 resources. The importance of representing NICs as objects for an object-oriented routing system is described in more detail further below.

As noted previously, the present invention is directed to a methodology for managing a distributed computing
15 environment. A resource is a portion of a computer system's physical units, a portion of a computer system's logical units, or a portion of the computer system's functionality that is identifiable or addressable in some manner to other physical or logical units within the system.

20 With reference now to **Figure 3**, a block diagram depicts components within the system management framework within a distributed computing environment such as that shown in **Figures 2D-2E**. A network contains gateway **300** and endpoints **301** and **302**. Gateway **302** runs ORB **304**. In general, an ORB
25 can support different services that are configured and run in conjunction with an ORB. In this case, distributed kernel services (DKS) include Network Endpoint Location Service (NELS) **306**, IP Object Persistence (IPOP) service **308**, and gateway service **310**.

30 The gateway service processes action objects, which are explained in more detail below, and directly communicates with endpoints or agents to perform management operations.

The gateway receives events from resources and passes the events to interested parties within the distributed system. The NELs works in combination with action objects and determines which gateway to use to reach a particular resource. A gateway is determined by using the discovery service of the appropriate topology driver, and the gateway location may change due to load balancing or failure of primary gateways.

Other resource level services may include an SNMP (Simple Network Management Protocol) service that provides protocol stacks, polling service, and trap receiver and filtering functions. The SNMP service can be used directly by certain components and applications when higher performance is required or the location independence provided by the gateways and action objects is not desired. A metadata service can also be provided to distribute information concerning the structure of SNMP agents.

The representation of resources within DKS allows for the dynamic management and use of those resources by applications. DKS does not impose any particular representation, but it does provide an object-oriented structure for applications to model resources. The use of object technology allows models to present a unified appearance to management applications and hide the differences among the underlying physical or logical resources. Logical and physical resources can be modeled as separate objects and related to each other using relationship attributes.

By using objects, for example, a system may implement an abstract concept of a router and then use this abstraction within a range of different router hardware. The common portions can be placed into an abstract router class while modeling the important differences in

subclasses, including representing a complex system with multiple objects. With an abstracted and encapsulated function, the management applications do not have to handle many details for each managed resource. A router usually
5 has many critical parts, including a routing subsystem, memory buffers, control components, interfaces, and multiple layers of communication protocols. Using multiple objects has the burden of creating multiple object identifiers (OIDs) because each object instance has its own OID.
10 However, a first order object can represent the entire resource and contain references to all of the constituent parts.

Each endpoint may support an object request broker, such as ORBs **320** and **322**, for assisting in remote
15 object-oriented operations within the DKS environment. Endpoint **301** contains DKS-enabled application **324** that utilizes object-oriented resources found within the distributed computing environment. Endpoint **302** contains target resource provider object or application **326** that
20 services the requests from DKS-enabled application **324**. A set of DKS services **330** and **334** support each particular endpoint.

Applications require some type of insulation from the specifics of the operations of gateways. In the DKS
25 environment, applications create action objects that encapsulate commands which are sent to gateways, and the applications wait for the return of the action object. Action objects contain all of the information necessary to run a command on a resource. The application does not need
30 to know the specific protocol that is used to communicate with the resource. The application is unaware of the location of the gateway because it issues an action object

into the system, and the action object itself locates and moves to the correct gateway. The location independence allows the NELS to balance the load between gateways independently of the applications and also allows the gateways to handle resources or endpoints that move or need to be serviced by another gateway.

The communication between a gateway and an action object is asynchronous, and the action objects provide error handling and recovery. If one gateway goes down or becomes overloaded, another gateway is located for executing the action object, and communication is established again with the application from the new gateway. Once the controlling gateway of the selected endpoint has been identified, the action object will transport itself there for further processing of the command or data contained in the action object. If it is within the same ORB, it is a direct transport. If it is within another ORB, then the transport can be accomplished with a "Moveto" command or as a parameter on a method call.

Queuing the action object on the gateway results in a controlled process for the sending and receiving of data from the IP devices. As a general rule, the queued action objects are executed in the order that they arrive at the gateway. The action object may create child action objects if the collection of endpoints contains more than a single ORB ID or gateway ID. The parent action object is responsible for coordinating the completion status of any of its children. The creation of child action objects is transparent to the calling application. A gateway processes incoming action objects, assigns a priority, and performs additional security challenges to prevent rogue action object attacks. The action object is delivered to the gateway that must convert the information in the action

object to a form suitable for the agent. The gateway manages multiple concurrent action objects targeted at one or more agents, returning the results of the operation to the calling application as appropriate.

5 In the preferred embodiment, potentially leasable target resources are Internet protocol (IP) commands, e.g. pings, and Simple Network Management Protocol (SNMP) commands that can be executed against endpoints in a managed region. Referring again to **Figures 2F** and **2G**, each NIC at a
10 gateway or an endpoint may be used to address an action object. Each NIC is represented as an object within the IPOP database, which is described in more detail further below.

15 The Action Object IP (AOIP) Class is a subclass of the Action Object Class. An AOIP object is the primary vehicle that establishes a connection between an application and a designated IP endpoint using a gateway or stand-alone service. In addition, the Action Object SNMP (AOSnmp) Class is also a subclass of the Action Object Class. An AOSnmp
20 object is the primary vehicle that establishes a connection between an application and a designated SNMP endpoint via a gateway or the gateway service. However, the present invention is primarily concerned with IP endpoints.

25 The AOIP class should include the following: a constructor to initialize itself; an interface to the NELS; a mechanism by which the action object can use the ORB to transport itself to the selected gateway; a security check verification of access rights to endpoints; a container for either data or commands to be executed at the gateway; a
30 mechanism by which to pass commands or classes to the appropriate gateway or endpoint for completion; and public methods to facilitate the communication between objects.

 The instantiation of an AOIP object creates a logical

circuit between an application and the targeted gateway or endpoint. This circuit is persistent until command completion through normal operation or until an exception is thrown. When created, the AOIP object instantiates itself
5 as an object and initializes any internal variables required. An AOIP may be capable of running a command from inception or waiting for a future command. A program that creates an AOIP object must supply the following elements: address of endpoints; function to be performed on the
10 endpoint; and data arguments specific to the command to be run. A small part of the action object must contain the return end path for the object. This may identify how to communicate with the action object in case of a breakdown in normal network communications. An action object can contain
15 either a class or object containing program information or data to be delivered eventually to an endpoint or a set of commands to be performed at the appropriate gateway. Action objects IP return back a result for each address endpoint targeted.

20 Using commands such as "Ping", "Trace Route", "Wake-On LAN", and "Discovery", the AOIP object performs the following services: facilitates the accumulation of metrics for the user connections; assists in the description of the topology of a connection; performs Wake-On LAN tasks using
25 helper functions; and discovers active agents in the network environment.

The NELS service finds a route to communicate between the application and the appropriate endpoint. The NELS service converts input to protocol, network address, and
30 gateway location for use by action objects. The NELS service is a thin service that supplies information discovered by the IPOP service. The primary roles of the NELS service are as follows: support the requests of

applications for routes; maintain the gateway and endpoint caches that keep the route information; ensure the security of the requests; and perform the requests as efficiently as possible to enhance performance.

5 For example, an application requires a target endpoint (target resource) to be located. The target is ultimately known within the DKS space using traditional network values, i.e. a specific network address and a specific protocol identifier. An action object is generated on behalf of an
10 application to resolve the network location of an endpoint. The action object asks the NELS service to resolve the network address and define the route to the endpoint in that network.

15 One of the following is passed to the action object to specify a destination endpoint: an EndpointAddress object; a fully decoded NetworkAddress object; or a string representing the IP address of the IP endpoint. In combination with the action objects, the NELS service determines which gateway to use to reach a particular
20 resource. The appropriate gateway is determined using the discovery service of the appropriate topology driver and may change due to load balancing or failure of primary gateways. An "EndpointAddress" object must consist of a collection of at least one or more unique managed resource IDs. A managed
25 resource ID decouples the protocol selection process from the application and allows the NELS service to have the flexibility to decide the best protocol to reach an endpoint. On return from the NELS service, an
30 "AddressEndpoint" object is returned, which contains enough information to target the best place to communicate with the selected IP endpoints. It should be noted that the address may include protocol-dependent addresses as well as protocol-independent addresses, such as the virtual private

network id and the IPOP Object ID. These additional addresses handle the case where duplicate addresses exist in the managed region.

When an action needs to be taken on a set of endpoints, the NELS service determines which endpoints are managed by which gateways. When the appropriate gateways are identified, a single copy of the action object is distributed to each identified gateway. The results from the endpoints are asynchronously merged back to the caller application through the appropriate gateways. Performing the actions asynchronously allows for tracking all results whether the endpoints are connected or disconnected. If the AOIP fails to execute on its target gateway, NELS is consulted to identify an alternative path for the command. If an alternate path is found, the action object IP is transported to that gateway and executed. It may be assumed that the entire set of commands within one action object IP must fail before this recovery procedure is invoked.

With reference now to **Figure 4**, a block diagram shows the manner in which data is stored by the IPOP (IP Object Persistence) service. IPOP service database **402** contains endpoint database table **404**, system database table **406**, and network database table **408**. Each table contains a set of topological objects (TopoObjects) for facilitating the leasing of resources at IP endpoints and the execution of action objects. Information within IPOP service database **402** allows applications to generate action objects for resources previously identified as IP objects through a discovery process across the distributed computing environment. **Figure 4** merely shows that the TopoObjects may be separated into a variety of categories that facilitate processing on the various objects. The separation of

physical network categories facilitates the efficient querying and storage of these objects while maintaining the physical network relationships in order to produce a graphical user interface of the network topology.

5 With reference now to **Figure 5A**, a block diagram shows the IPOP service in more detail. In the preferred embodiment of the present invention, an IP driver subsystem is implemented as a collection of software components for discovering, i.e. detecting, IP "objects", i.e. IP networks,
10 IP systems, and IP endpoints by using physical network connections. This discovered physical network is used to create topology data that is then provided through other services via topology maps accessible through a graphical user interface (GUI) or for the manipulation of other
15 applications. The IP driver system can also monitor objects for changes in IP topology and update databases with the new topology information. The IPOP service provides services for other applications to access the IP object database.

IP driver subsystem **500** contains a conglomeration of
20 components, including one or more IP drivers **502**. Every IP driver manages its own "scope", which is described in more detail further below, and every IP driver is assigned to a topology manager within topology service **504**, which can serve more than one IP driver. Topology service **504** stores
25 topology information obtained from discovery controller **506**. The information stored within the topology service may include graphs, arcs, and the relationships between nodes determined by IP mapper **508**. Users can be provided with a GUI to navigate the topology, which can be stored within a
30 database within the topology service.

IPOP service **510** provides a persistent repository **512** for discovered IP objects; persistent repository **512**

contains attributes of IP objects without presentation information. Discovery controller **506** detects IP objects in Physical IP networks **514**, and monitor controller **516** monitors IP objects. A persistent repository, such as IPOP database **512**, is updated to contain information about the discovered and monitored IP objects. IP driver may use temporary IP data store component **518** and IP data cache component **520** as necessary for caching IP objects or storing IP objects in persistent repository **512**, respectively. As discovery controller **506** and monitor controller **516** perform detection and monitoring functions, events can be written to network event manager application **522** to alert network administrators of certain occurrences within the network, such as the discovery of duplicate IP addresses or invalid network masks.

External applications/users **524** can be other users, such as network administrators at management consoles, or applications that use IP driver GUI interface **526** to configure IP driver **502**, manage/unmanage IP objects, and manipulate objects in persistent repository **512**. Configuration service **528** provides configuration information to IP driver **502**. IP driver controller **530** serves as central control of all other IP driver components.

Referring back to **Figure 2G**, a network discovery engine is a distributed collection of IP drivers that are used to ensure that operations on IP objects by gateways **260**, **270**, and **280** can scale to a large installation and provide fault-tolerant operation with dynamic start/stop or reconfiguration of each IP driver. The IPOP service stores and retrieves information about discovered IP objects; to do so, the IPOP service uses a distributed database in order to efficiently service query requests by a gateway to determine

routing, identity, or a variety of details about an endpoint. The IPOP service also services queries by the topology service in order to display a physical network or map them to a logical network, which is a subset of a physical network that is defined programmatically or by an administrator. IPOP fault tolerance is also achieved by distribution of IPOP data and the IPOP service among many Endpoint ORBs.

One or more IP drivers can be deployed to provide distribution of IP discovery and promote scalability of IP driver subsystem services in large networks where a single IP driver is not sufficient to discover and monitor all IP objects. Each IP driver performs discovery and monitoring on a collection of IP resources within the driver's "scope". A driver's scope, which is explained in more detail below, is simply the set of IP subnets for which the driver is responsible for discovering and monitoring. Network administrators generally partition their networks into as many scopes as needed to provide distributed discovery and satisfactory performance.

A potential risk exists if the scope of one driver overlaps the scope of another, i.e. if two drivers attempt to discover/monitor the same device. Accurately defining unique and independent scopes may require the development of a scope configuration tool to verify the uniqueness of scope definitions. Routers also pose a potential problem in that while the networks serviced by the routers will be in different scopes, a convention needs to be established to specify to which network the router "belongs", thereby limiting the router itself to the scope of a single driver.

Some ISPs may have to manage private networks whose addresses may not be unique across the installation, like 10.0.0.0 network. In order to manage private networks

properly, first, the IP driver has to be installed inside the internal networks in order to be able to discover and manage the networks. Second, since the discovered IP addresses may not be unique across an entire installation that consists of multiple regions, multiple customers, etc., a private network ID has to be assigned to the private network addresses. In the preferred embodiment, the unique name of a subnet becomes "privateNetworkId\subnetAddress". Those customers that do not have duplicate networks address can just ignore the private network ID; the default private network ID is 0.

If Network Address Translator (NAT) is installed to translate the internal IP addresses to Internet IP addresses, users can install the IP drivers outside of NAT and manage the IP addresses inside the NAT. In this case, an IP driver will see only the translated IP addresses and discover only the IP addresses translated. If not all IP addresses inside the NAT are translated, an IP driver will not be able to discover all of them. However, if IP drivers are installed this way, users do not have to configure the private network within the IP driver's scope.

Scope configuration is important to the proper operation of the IP drivers because IP drivers assume that there are no overlaps in the drivers' scopes. Since there should be no overlaps, every IP driver has complete control over the objects within its scope. A particular IP driver does not need to know anything about the other IP drivers because there is no synchronization of information between IP drivers. The configuration service provides the means to allow the DKS components to store and retrieve configuration information for a variety of other services from anywhere in the networks. In particular, the scope configuration will be stored in the configuration services so that IP drivers

and other applications can access the information.

The ranges of addresses that a driver will discover and monitor are determined by associating a subnet address with a subnet mask and associating the resulting range of addresses with a subnet priority. An IP driver is a collection of such ranges of addresses, and the subnet priority is used to help decide the system address. A system can belong to two or more subnets, such as is commonly seen with a Gateway. The system address is the address of one of the NICs that is used to make SNMP queries. A user interface can be provided, such as an administrator console, to write scope information into the configuration service. System administrators do not need to provide this information at all, however, as the IP drivers can use default values.

An IP driver gets its scope configuration information from the configuration service, which may be stored using the following format:

```
scopeID=driverID,anchorname,subnetAddress:subnetMask[
:privateNetworkId:privateNetworkName:subnetPriority][,
subnetAddress:subnetMask:privateNetworkId:privateNetworkName
:subnetPriority]]
```

Typically, one IP driver manages only one scope. Hence, the "scopeID" and "driverID" would be the same. However, the configuration can provide for more than one scope managed by the same driver. "Anchorname" is the name in the name space in which the topology service will put the IP driver's network objects.

A scope does not have to include an actual subnet configured in the network. Instead, users/administrators can group subnets into a single, logical scope by applying a

bigger subnet mask to the network address. For example, if a system has subnet "147.0.0.0" with mask of "255.255.0.0" and subnet "147.1.0.0" with a subnet mask of "255.255.0.0", the subnets can be grouped into a single scope by applying a mask of "255.254.0.0". Assume that the following table is the scope of IP Driver 2. The scope configuration for IP Driver 2 from the configuration service would be:

2=2,ip,147.0.0.0:255.254.0.0,146.100.0.0:255.255.0.0,69.0.0.0:255.0.0.0.

Subnet address	Subnet mask
147.0.0.0	255.255.0.0
147.1.0.0	255.255.0.0
146.100.0.0	255.255.0.0
69.0.0.0	255.0.0.0

In general, an IP system is associated with a single IP address, and the "scoping" process is a straightforward association of a driver's ID with the system's IP address.

Routers and multi-homed systems, however, complicate the discovery and monitoring process because these devices may contain interfaces that are associated with different subnets. If all subnets of routers and multi-homed systems are in the scope of the same driver, the IP driver will manage the whole system. However, if the subnets of routers and multi-homed systems are across the scopes of different drivers, a convention is needed to determine a dominant interface: the IP driver that manages the dominant interface will manage the router object so that the router is not being detected and monitored by multiple drivers; each interface is still managed by the IP driver determined by its scope; the IP address of the dominant interface will be assigned as the system address of the router or multi-homed

system; and the smallest (lowest) IP address of any interface on the router will determine which driver includes the router object within its scope.

Users can customize the configuration by using the subnet priority in the scope configuration. The subnet priority will be used to determinate the dominant interface before using the lowest IP address. If the subnet priorities are the same, the lowest IP address is then used. Since the default subnet priority would be "0", then the lowest IP address would be used by default.

With reference now to **Figure 5B**, a network diagram depicts a network with a router that undergoes a scoping process. IP driver D1 will include the router in its scope because the subnet associated with that router interface is lower than the other three subnet addresses. However, each driver will still manage those interfaces inside the router in its scope. Drivers D2 and D3 will monitor the devices within their respective subnets, but only driver D1 will store information about the router itself in the IPOP database and the topology service database.

If driver D1's entire subnet is removed from the router, driver D2 will become the new "owner" of the router object because the subnet address associated with driver D2 is now the lowest address on the router. Because there is no synchronization of information between the drivers, the drivers will self-correct over time as they periodically rediscover their resources. When the old driver discovers that it no longer owns the router, it deletes the router's information from the databases. When the new driver discovers the router's lowest subnet address is now within its scope, the new driver takes ownership of the router and updates the various databases with the router's information. If the new driver discovers the change before the old driver

has deleted the object, then the router object may be briefly represented twice until the old owner deletes the original representation.

There are two kinds of associations between IP objects.

5 One is "IP endpoint in IP system" and the other is "IP endpoint in IP network". The implementation of associations relies on the fact that an IP endpoint has the object IDs (OIDs) of the IP system and the IP network in which it is located. An IP driver can partition all IP networks, IP
10 Systems, and IP endpoints into different scopes. A network and all its IP endpoints will always be assigned in the same scope. However, a router may be assigned to an IP driver, but some of its interfaces are assigned to different IP drivers. The IP drivers that do not manage the router but
15 manage some of its interfaces will have to create interfaces but not the router object. Since those IP drivers do not have a router object ID to assign to its managed interfaces, they will assign a unique system name instead of object ID in the IP endpoint object to provide a link to the system
20 object in a different driver.

Because of the inter-scope association, when the IP Object Persistence Service (IPOP) is queried to find all the IP endpoints in system, it will have to search not only IP endpoints with the system ID but also IP endpoints with its
25 system name. If a distributed IP Object Persistence Service is implemented, the service has to provide extra information for searching among its distributed instances.

An IP driver may use a security service to check access to IP objects. In order to handle large number of objects,
30 the security service requires the users to provide a naming hierarchy as the grouping mechanism. **Figure 5C**, described below, shows a security naming hierarchy of IP objects. An IP driver has to allow users to provide security down to the

object level and to achieve high performance. In order to achieve this goal, the concepts of "anchor" and "unique object name" are introduced. An anchor is a name in the naming space which can be used to plug in IP networks.

- 5 Users can define, under the anchor, scopes that belong to the same customer or to a region. The anchor is then used by the security service to check if a user has access to the resource under the anchor. If users want a security group defined inside a network, the unique object name is used. A
10 unique object name is in the format of:

IP network - privateNetworkID/binaryNetworkAddress

IP system - privateNetworkID/binaryIPAddress/system

IP endpoint- privateNetworkID/binaryNetworkAddress/endpoint

For example:

- 15 A network "146.84.28.0:255.255.255.0" in privateNetworkID 12 has unique name:

12/1/0/0/1/0/0/1/0/0/1/0/1/0/1/0/0/0/0/0/1/1/1/0/0/0.

A system "146.84.28.22" in privateNetworkID 12 has unique name:

- 20 12/1/0/0/1/0/0/1/0/0/1/0/1/0/1/0/0/0/0/0/1/1/1/0/0/0/0/0/1/0/1/1/0/system.

An endpoint "146.84.28.22" in privateNetworkId 12 has unique name:

- 25 12/1/0/0/1/0/0/1/0/0/1/0/1/0/1/0/0/0/0/0/1/1/1/0/0/0/0/0/1/0/1/1/0/endpoint.

By using an IP-address, binary-tree, naming space, one can group all the IP addresses under a subnet in the same naming space that need to be checked by the security service.

- 30 For example, one can set up all IP addresses under subnet "146.84.0.0:255.255.0.0" under the naming space
12/1/0/0/1/0/0/1/0/0/1/0/1/0/1/0/0
and set the access rights based on this node name.

With reference now to **Figure 5C**, the IP Object Security Hierarchy is depicted. Under the root, there are two fixed security groups. One is "default" and the other is "all". The name of "default" can be configured by within the configuration service. Users are allowed to configure which subnets are under which customer by using the configuration service.

Under the first level security group, there are router groups and subnet groups. Those systems that have only one interface will be placed under the subnets group. Those systems that have more than one interface will be placed under the router group; a multi-home system will be placed under the router group.

Every IP object has a "securityGroup" field to store which security group it is in. The following describes how security groups are assigned.

When a subnet is created and it is not configured for any customers, its securityGroup is "/default/subnet/subnetAddress". When a subnet is created and it is configured in the "customer1" domain, its "securityGroup" value is "/customer1/subnet/subnetAddress".

When an IP endpoint is created and it is not configured for any customers, its "securityGroup" value is "/default/subnet/subnetAddress". The subnet address is the address of the subnet in which the IP endpoint is located. When an IP endpoint is created and it is configured in the "customer1" domain, its "securityGroup" value is "/customer1/subnet/subnetAddress". The subnet address is the address of the subnet in which the IP endpoint is located.

When a single interface IP system is created, it has the same "securityGroup" value that its interface has. When a router or multi-home system is created, the

"securityGroup" value depends on whether all of the interfaces in the router or multi-home system are in the same customer group or not. If all of the interfaces of the router or multi-home system are in the same customer group, e.g., "customer1", its "securityGroup" value is
5 "/customer1/router". If the interfaces of the router or multi-home system are in more than one domain, its "securityGroup" value is "/all/router".

These are the default security groups created by an IP driver. After the security group is created for an object,
10 IP driver will not change the security group unless a customer wants to change it.

The IP Monitor Controller, shown in **Figure 5A**, is responsible for monitoring the changes of IP topology and objects; as such, it is a type of polling engine, which is
15 discussed in more detail further below. An IP driver stores the last polling times of an IP system in memory but not in the IPOP database. The last polling time is used to calculate when the next polling time will be. Since the last polling times are not stored in the IPOP database, when
20 an IP Driver initializes, it has no knowledge about when the last polling times occurred. If polling is configured to occur at a specific time, an IP driver will do polling at the next specific polling time; otherwise, an IP driver will spread out the polling in the polling interval.
25

The IP Monitor Controller uses SNMP polls to determine if there have been any configuration changes in an IP system. It also looks for any IP endpoints added to or deleted from an IP system. The IP Monitor Controller also
30 monitors the statuses of IP endpoints in an IP system. In order to reduce network traffic, an IP driver will use SNMP to get the status of all IP endpoints in an IP system in one query unless an SNMP agent is not running on the IP system.

Otherwise, an IP driver will use "Ping" instead of SNMP. An IP driver will use "Ping" to get the status of an IP endpoint if it is the only IP endpoint in the system since the response from "Ping" is quicker than SNMP.

5 With reference now to **Figure 6**, a block diagram shows a set of components that may be used to implement scope-based security access in the present invention. Login security subsystem **602** provides a typical authentication service, which may be used to verify the identity of users during a login process. All-user database **604** provides information about all users in the DKS system, and active user database **606** contains information about users that are currently logged into the DKS system.

10 Discovery engine **608**, similar to discovery controller **506** in **Figure 5**, detects IP objects within an IP network. Polling engine, similar to monitor controller **516** in **Figure 5**, monitors IP objects. A persistent repository, such as IPOP database **612**, is updated to contain information about the discovered and monitored IP objects. IPOP also obtains the list of all users from the security subsystem which queries its all-users database **604** when initially creating a DSC (Device Scope Context) object. During subsequent operations to map the location of a user to an ORB, the DSC manager will query the active user database **606**.

20 The DSC manager queries IPOP for all endpoint data during the initial creation of DSCs and any additional information needed, such as decoding an ORB address to an endpoint in IPOP and back to a DSC using the IPOPOid, the ID of a network object as opposed to an address.

30 An administrator can fill out the security information with respect to access user or endpoint access and designate which users and endpoints will have a DSC. If not

configured by the administrator, a default DSC will be used. While not all endpoints will have an associated DSC, IPOP endpoint data **612**, login security subsystem **602**, and security information **604** are needed in order to create the initial DSCs.

The DSC manager, acting as a DSC data consumer, explained in more detail further below, then listens on this data waiting for new endpoints or users or changes to existing ones. DSC configuration changes are advertised by a responsible network management application, such as a configuration service. Some configuration changes will trigger the creation of more DSCs, while others will cause DSC data in the DSC database to be merely updated.

All DSCs are stored in DSC database **618** by DSC creator **616**, which also fetches DSCs upon configuration changes in order to determine whether or not a DSC already exists. The DSC manager primarily fetches DSCs from DSC database **618**, but also adds runtime information, such as ORB ID.

With reference now to **Figure 7A**, a flowchart depicts a portion of an initialization process in which a network management system prepares a security subsystem for user access to network-related objects. The process begins with the assumption that a network administrator has already performed configuration processes on the network such that configuration information is properly stored where necessary. The discovery engine performs a discovery process to identify IP objects and stores these in the IPOP persistence storage (step **702**).

The DSC creator in the DSC manager generates "initial" DSC objects and stores these within the DSC database (step **704**).

A source user then performs a login on a source

endpoint (step **706**). An application may use a resource, termed a target resource, located somewhere within the distributed system, as described above. Hence, the endpoint on which the target resource is located is termed the "target endpoint". The endpoint on which the application is executing is termed the "source endpoint" to distinguish it from the "target endpoint", and the user of the application is termed the "source user".

As part of the login process, the security subsystem updates the active user database for the ORB on which the application is executing (step **708**). The initialization process is then complete.

With reference now to **Figure 7B**, a flowchart depicts further detail of the initialization process in which the DSC objects are initially created and stored. **Figure 7B** provides more detail for step **704** shown in **Figure 7A**.

The process shown in **Figure 7B** provides an outline for the manner in which the DSC manager sets up associations between users and endpoints and between endpoints and endpoints. These associations are stored as special objects termed "DSC objects". A DSC object is created for all possible combinations of users and endpoints and for all possible combinations of endpoints and endpoints. From one perspective, each DSC object provides guidance on a one-to-one authorization mapping between two points in which a first point (source point) can be a user or an endpoint and a second point (target point) is an endpoint.

Figure 7B depicts the manner in which the DSC manager initially creates and stores the DSC objects for subsequent use. At some later point in time, a user associated with an application executing on a source endpoint may request some type of network management action at a target endpoint, or a

network management application may automatically perform an action at a target endpoint on behalf of a user that has logged into a source endpoint. Prior to completing the necessary network management task, the system must check whether the source user has the proper authorization to perform the task at the target endpoint.

Not all network monitoring and management tasks require that a user initiate the task. Some network management applications will perform tasks automatically without a user being logged onto the system and using the network management application. At some point in time, an application executing on a source endpoint may automatically attempt to perform an action at a target endpoint. Prior to completing the necessary network management task, the system must check whether the source endpoint has the proper authorization to perform the task at the target endpoint in a manner similar to the case of the source user performing an action at a target endpoint.

When the system needs to perform an authorization process, the previously created and stored DSC objects can be used to assist in the authorization process. By storing the DSC objects within a distributed database, a portion of the authorization process has already been completed. Hence, the design of the system has required a tradeoff between time and effort invested during certain system configuration processes and time and effort invested during certain runtime processes. A configuration process may require more time to complete while the DSC objects are created, but runtime authorization processes become much more efficient.

The DSC objects are created and stored within a distributed database during certain configuration processes throughout the system. A new system usually undergoes a

significant installation and configuration process.

However, during the life of the system, endpoints may be added or deleted, and each addition or deletion generally requires some type of configuration process. Hence, the DSC objects can be created or deleted as needed on an ongoing basis.

The network management framework also provides an additional advantage by storing the DSC objects within a highly distributed database. Because the present invention provides a network management system for an application framework over a highly distributed data processing system, the system avoids centralized bottlenecks that could occur if the authorization processes had to rely upon a centralized security database or application. The first DSC fetch requires relatively more time than might be required with a centralized subsystem. However, once fetched, a DSC is cached until listeners on the configuration data signal that a change has occurred, at which point the DSC cache must be flushed.

The process in **Figure 7B** begins with the DSC manager fetching endpoint data from the IPOP database (step **710**). The IPOP database was already populated with IP objects during the discovery process, as mentioned in step **702** of **Figure 7A**. The DSC manager fetches user data from the all-user database in the security subsystem (step **712**). Configuration data is also fetched from the configuration service database or databases (step **714**), such as ORB IDs that are subsequently used to fetch the ORB address. A network administration application will also use the configuration service to store information defined by the administrator. The DSC manager then creates DSC objects for each user/endpoint combination (step **716**) and for each

endpoint/endpoint combination (step **718**), and the DSC object creation process is then complete.

With reference now to **Figure 7C**, a flowchart depicts further detail of the initial DSC object creation process in which DSC objects are created and stored for an endpoint/user combination. **Figure 7C** provides more detail for step **716** in **Figure 7B**. The process shown in **Figure 7C** is a loop through all users that can be identified within the all-user database. In other words, a set of user accounts or identities have already been created and stored over time. However, all users that have been authorized to use the system do not have the same authorized privileges. The process shown in **Figure 7C** is one of the first steps towards storing information that will allow the system to differentiate between users so that it can adaptively monitor the system based partially on the identity of the user for which the system is performing a monitoring task.

The process in **Figure 7C** begins by reading scope data for a target endpoint from the IPOP database (step **720**). The DSC creator within the DSC manager then reads scope data for a source user from the IPOP database (step **722**). A determination is then made as to whether or not the source user is allowed to access the target endpoint (step **724**). This determination can be made in the following manner. After the initial DSC is obtained, the source user information is used to make an authorization call to the security subsystem as to whether or not the source user has access to the security group defined in the DSC. It may be assumed that the security system can perform this function efficiently, although the present invention does not depend on auto-generation of security names or security trees. The present invention should not be understood as depending upon

any particular implementation of security authorization.

If not, then the process branches to check whether another user identity should be processed. If the source user is allowed to access the target endpoint, then a DSC object is created for the current source user and current target endpoint that are being processed (step **726**). The DSC object is then stored within the DSC database (step **728**), and a check is made as to whether or not another source user identity requires processing (step **729**). If so, then the process loops back to get and process another user, otherwise the process is complete.

With reference now to **Figure 7D**, a flowchart depicts further detail of the initial DSC object creation process in which DSC objects are created and stored for an endpoint/endpoint combination. **Figure 7D** provides more detail for step **718** in **Figure 7B**. The process shown in **Figure 7D** is a loop through all endpoints that can be identified within the IPOP database; the IPOP database was already populated with IP objects during the discovery process, as mentioned in step **702** of **Figure 7A**. During runtime operations, an application executing on a source endpoint may attempt to perform an action at a target endpoint. However, not all endpoints within the system have access to requesting actions at all other endpoints within the system. The network management system needs to attempt to determine whether or not a source endpoint is authorized to request an action from a target endpoint. The process shown in **Figure 7D** is one of the first steps towards storing information that will allow the system to differentiate between endpoints so that it can monitor the system based partially on the identity of the source endpoint for which the system is performing a monitoring task.

The process in **Figure 7D** begins by reading scope data for a target endpoint from the IPOP database (step **730**). The DSC creator within the DSC manager then reads scope data for a source endpoint from the IPOP database (step **732**). A
5 determination is then made as to whether or not the source endpoint is allowed to access the target endpoint (step **734**) based on the scope defined in the DSC. For example, a simple scope of X.Y.Z.* will allow an address of X.Y.Z.Q access. If not, then the process branches to check whether
10 another source endpoint should be processed. If the source endpoint is allowed to access the target endpoint, then a DSC object is created for the source endpoint and target endpoint that are currently being processed (step **736**). The DSC object is then stored within the DSC database (step
15 **738**), and a check is made as to whether or not another source endpoint requires processing (step **739**). If so, then the process loops back to get and process another endpoint, otherwise the process is complete.

The components and subsystems described above with
20 respect to **Figures 6-7D** are used to restrict administrative user access to various operations and functionality within the network management framework. The following description of **Figures 8A-14B** describe particular operations and functionality that may be available to administrative users
25 within the network management framework. In particular, **Figures 8A-14B** show various ways in which scopes and anchors are used to perform certain tasks within a single network management framework that is being used to manage a multi-customer environment. More specifically, **Figures**
30 **8A-9B** depict a manner in which an administrative user may view the topology of a set of network-related objects that are being managed by the network management framework,

whereas **Figures 10A-14B** depict a process for configuring information within the network management framework so that it may manage the networks of multiple customers.

As described above, an IP driver subsystem is implemented as a collection of software components for discovering, i.e. detecting, network "objects", such as IP networks, IP systems, and IP endpoints by using physical network connections. The collected data is then provided through other services via topology maps accessible through a GUI or for the manipulation of other applications. The IP driver system can also monitor objects for changes in IP topology and update databases with the new topology information. The IPOP service provides services for other applications to access the IP object database.

Referring again to **Figure 5A**, IP driver subsystem **500** contains a conglomeration of components, including one or more IP drivers **502**. Every IP driver manages its own "scope", and every IP driver is assigned to a topology manager within topology service **504**, which stores topology information obtained from discovery controller **506**. The information stored within the topology service may include graphs, arcs, and the relationships between nodes determined by IP mapper **508**. Users can be provided with a GUI to navigate the topology, which can be stored within a database within the topology service.

The topology service provides a framework for DKS-enabled applications to manage topology data. In a manner similar to the IPOP service, the topology service is actually a cluster of topology servers distributed throughout the network. All of the functions of the topology service are replicated in each topology server. Therefore, a client can attach to any server instance and

perform the same tasks and access the same objects. Each topology-related database is accessible from more than one topology server, which enables the topology service to recover from a server crash and provide a way to balance the load on the service.

Topology clients create an instance of a TopoClientService class. As part of creating the TopoClientService instance, the class connects to one of the topology servers. The topology server assumes the burden of consolidating all of the topology information distributed over the different topology servers into a single combined view. The topology service tracks changes in the objects of interest for each client and notifies a client if any of the objects change.

The topology service may have a server-cluster design for maximizing availability. As long as there is at least one instance of the topology server running, then clients have access to topology objects and services. The topology service design allows for servers to occasionally fail. Each server is aware of the state of all the other server instances. If one instance fails, the other servers know immediately and automatically begin to rebuild state information that was lost by the failed server. A client's TopoClientService instance also knows of the failure of the server to which it is connected and re-connects to a different server. The objects residing at a failed topology server are migrated to the other topology servers when the drivers owning those objects have re-located.

The topology service is scalable, which is important so that the service may be the central place for all network topology objects for all of the different DKS-related applications in order to provide efficient service for millions of objects. As the number of clients, drivers, and

objects increase, an administrator can create more instances of topology servers, thereby balancing the workload. Using the server cluster approach, any growth in the number of clients, drivers, and objects is accommodated by simply adding more servers. The existing servers detect the additional instances and begin to move clients and drivers over to the new instances. The automated load-balancing is achieved because the clients and objects are not dependent on any one server instance.

In order to provide a service for an entire enterprise, all of the enterprise's objects generally do not reside in the same database. There may be many reasons that make it undesirable to require that all topology objects be stored in the same database instance. For example, a database simply may not be reachable across an international boundary, or the volume of information going into the database may exceed a single database's capacity.

Therefore, the topology objects may span databases, and there may be relationships between objects in different databases. However, it may be assumed that all topology objects in a domain reside in the same database. For example, all IP objects for a single enterprise do not necessarily reside in the same database as the enterprise's IP space may be split into many domains, e.g., a southwest IP domain and a northeast IP domain, but each domain may reside in different databases and still have relations between their objects. Hence, it is possible to have two objects related to each other even though they are in different databases. Since the name of the domain is part of the id of the object, each object can be uniquely identified within the entire topology service.

When an application is installed and configured to use the DKS services, the application provides some information

to the topology service about the different types of TopoObjects it will be creating. This class information closely resembles the network entities that a driver will be managing. For example, an IP application works with

5 Network, System, and Endpoint resource types, as described previously with respect to **Figure 4**. Giving TopoObjects a resource type enables client applications to identify, group, and query the databases based on domain-specific types. Each resource type may have many different types of

10 relations that the driver may create, and the most common type may be the containment relation, which shows the containment hierarchy of a domain. Each relation type has a corresponding ViewData object, which provides information that an administrative console needs to create a view of the

15 TopoObjects. For example, the ViewData object may contain members like BackgroundColor and LayoutType that are used to construct a graphical display of the object. Relations can be created between any two TopoObjects. The TopoObjects can be owned by the same driver, different drivers in the

20 domain, or even drivers in different domains.

With reference now to **Figure 8A**, a flowchart depicts a process for creating topology data. The process begins when one or more discovery engines scan physical networks until a new device is found (step **802**). A determination is made as

25 to whether or not a network object exists for the network in which the endpoint has been found (step **804**). If not, then a network object is created (step **806**), otherwise the process continues.

In either case, a determination is then made as to

30 whether or not a system object exists for the system in which the endpoint has been found (step **808**). If not, then a system object is created (step **810**), otherwise the process

continues. In either case, an endpoint object is then created for the discovered device (step **812**), and all of the created objects are then stored within the IPOP database (step **814**). The created objects are then mapped into the
5 current topology (step **816**), and the topology service creates topology objects (step **818**) and stores them within the topology database (step **820**). The process of discovering a physical network or device and storing appropriate information is then complete.

10 With reference now to **Figure 8B**, a flowchart depicts a process for listening for physical network changes that affect topology objects. The process begins with a determination of whether or not one or more polling engines has found a system or device that has failed (step **832**). If
15 not, then a determination is made as to whether or not a new device has been discovered (step **834**). If not, then the process loops back to continue monitoring the networks.

If either a new device is discovered or a device has failed, then the appropriate changes are made to the objects representing the physical devices that have been affected by
20 updating the IPOP database (step **836**). For example, if a new device is found, then appropriate steps are made to create the necessary objects in a manner similar to steps **804-820** in **Figure 8A**. A determination is then made as to
25 whether or not the detected change affects the topology (step **838**), and if not, then the process is complete. If the topology has been affected, then the topology database is updated as necessary (step **840**), and the process of listening for network changes and reflecting those changes
30 within the topology is complete.

With reference now to **Figure 9A**, a figure depicts a graphical user interface window that may be used by a

network or system administrator to view the topology of a network that is being monitored. Window **900** depicts a simple network showing router device **902**, endpoint **904**, and endpoint **906**. In addition, line **908** shows a relation
5 between endpoint **904** and router **902**, and line **910** shows a relation between endpoint **906** and router **902**. Each of the icons **902-906** represents a TopoObject that is maintained by the topology service.

With reference now to **Figure 9B**, a figure depicts a
10 graphical user interface window that shows the topology of a network that has changed. Window **930** in **Figure 9B** shows the same network as depicted within window **900** of **Figure 9A** except that an endpoint has failed and has been deleted from the current topology. Window **930** depicts a simple network
15 showing router device **932**, endpoint **934**, and line **936** for the relation between endpoint **934** and router **932**.

As noted previously, **Figures 8A-9B** depict one administrative operation that may be performed in conjunction with the present invention, whereas **Figures**
20 **10A-14B** depict another administrative operation; these examples are included herein to provide a context in which the network management framework uses IP drivers, scopes, anchors, and other framework components in order to provide a robust network management framework for supporting the
25 management of the networks of multiple customers in an integrated manner.

One particular problem that a robust network management framework for a service provider must confront is the fact that many customers of a service provider may have
30 software-based and/or hardware-based network address translators, or NATs. Each network address within a given domain serviced by a NAT can be assumed to be unique.

However, across multiple NATs, each network address within the entire set of network addresses cannot be assumed to be unique. In fact, the potential for duplicate addresses over such a large, highly distributed network is quite high.

5 Even if the service provider is managing only one customer within a particular network management environment, the same problem might also exist because a single customer may operate multiple NATs for multiple networks. This type of problem is illustrated in more detail in **Figures 10A-10B**.

10 With reference now to **Figure 10A**, a block diagram depicts a known configuration of software and/or hardware network components linking multiple networks. A computer-type device is functioning as firewall/NAT **1020**, which is usually some combination of software and hardware,
15 to monitor data traffic from external network **1022** to internal protected network **1024**. Firewall **1020** reads data received by network interface card (NIC) **1026** and determines whether the data should be allowed to proceed onto the internal network. If so, then firewall **1020** relays the data
20 through NIC **1028**. The firewall can perform similar processes for outbound data to prevent certain types of data traffic from being transmitted, such as HTTP (Hypertext Transport Protocol) Requests to certain domains.

25 More importantly for this context, the firewall can prevent certain types of network traffic from reaching devices that reside on the internal protected network. For example, the firewall can examine the frame types or other information of the received data packets to stop certain types of information that has been previously determined to
30 be harmful, such as virus probes, broadcast data, pings, etc. As an additional example, entities that are outside of the internal network and lack the proper authorization may

attempt to discover, through various methods, the topology of the internal network and the types of resources that are available on the internal network in order to plan electronic attacks on the network. Firewalls can prevent these types of discovery practices.

While firewalls may prevent certain entities from obtaining information from the protected internal network, firewalls may also present a barrier to the operation of legitimate, useful processes. For example, in order to ensure a predetermined level of service, benevolent processes may need to operate on both the external network and the protected internal network; a customer system is more efficiently managed if the management software can dynamically detect and dynamically configure hardware resources as they are installed, rebooted, etc. Various types of discovery processes, status polling, status gathering, etc., may be used to get information about the customer's large, dynamic, distributed processing system. This information is then used to ensure that quality-of-service guarantees to the customer are being fulfilled. However, firewalls might block these system processes, especially discovery processes.

Firewall/NAT **1020** also performs network address translation between addresses on external network **1022** and addresses on internal network **1024**. In the example, system **1030** connects to internal network **1024** via NIC **1032**; system **1034** connects to internal network **1024** via NIC **1036**; and system **1038** connects to internal network **1024** via NIC **1040**. Each NIC has its own MAC (Media Access Control layer) address, which is a guaranteed unique hardware address in the NIC that is used to address data packets to and from the system that is using a given NIC. Network Address

Translator (NAT) **1020** presents all of the systems on internal network **1024** to external network **1022** with a single, public, IP address. However, systems **1030**, **1034**, and **1038** have addresses which are unique within internal network **1024**. NAT **1020** retrieves the addresses within the data packets flowing between the internal network and the external network, translates the addresses between the two domains, stores the addresses back into the data packets, and forwards the data packets.

The internal network supports a private address space with globally non-unique address, whereas the external network represents a public address space of globally unique addresses. A NAT device is used to manage the connectivity of the private network with the outside world; the NAT device bridges the internal network and the external network and converts addresses between the two address spaces. Within a private network behind a NAT, an enterprise may have its own private address space without concern for integrating the private address space with the global Internet, particularly with the predominant IPv4 address space that is currently in use.

NATs are helpful for certain enterprises that do not require full connectivity for all of its devices. However, NATs present barriers for certain functionality. A NAT must have high performance in order to perform address translation on all data packets that are sent and received by a private network. In addition, a network management framework for a highly distributed system may be forced to coordinate its actions across multiple NAT devices within a single customer or across multiple customers. For example, systems **1030**, **1034**, and **1038** have addresses which are unique within internal network **1024**. However, another internal

network within the same enterprise may duplicate the addresses that are used within internal network **1024**.

When contending with multiple NATs, the network management framework cannot assume uniqueness among private network addresses. In some prior art systems, it would have been straightforward to use the private network address of a device as a unique key within the network management applications because the private network address has a unique association with a networked device. In a highly distributed system, the network management framework needs to store many data items in an efficient manner yet cannot rely upon a scheme that uses the private network addresses as unique keys for managing those data items.

Future IT solutions may not need to confront the same problems because the Internet is moving towards using a new standard IP protocol known as IP Version 6 (IPv6) that will have a much larger address space. However, a current network management solution must confront legacy issues of maintaining currently installed hardware.

Prior art solutions have generally included dedicated boxes or devices that perform address translation. These solutions tend to be specific modifications to an operating system or kernel, which reduces the benefit of having standardized implementations of software platforms. In other words, some applications may not be compatible with the solution. In addition, such solutions may require installing a dedicated device for each system, which is prohibitive.

With reference now to **Figure 10B**, a block diagram depicts a service provider connected to two customers that each have subnets that may contain duplicate network addresses. As noted above, multiple internal networks within a highly distributed data processing system may

contain duplicate addresses. Service provider **1050** manages networks and applications for multiple customers and stores its data within multi-customer database **1052**. Customer **1054** has a network of devices that includes subnet **1056** that
5 connect with the larger network through NAT **1058**; customer **1064** has a network of devices that includes subnet **1066** that connect with the larger network through NAT **1068**. Duplicate network addresses could appear within subnets **1056** and **1066**. In order to provide certain services in a seamless fashion
10 such that both customers can be managed by the service provider as a single logical network, the service provider requires a network management framework that can handle duplicate network addresses.

The network management framework that is described
15 herein can manage multiple networks over which duplicate addresses might appear, e.g., as shown in **Figure 10B**, such that the distributed network management framework is operable across multiple NATs. The manner in which the network management is performed is described further below
20 in more detail.

With reference now to **Figure 11A**, a block diagram shows a set of components that may be used to implement multi-customer management across multiple networks in which duplicate addresses may be present. **Figure 11A** depicts
25 components that are similar to components introduced in other figures above. User security subsystem **1106** provides a user authentication and authorization service, which may be used to verify the identity of users, such as administrators, during a login process and during
30 administrative operations. IP drivers **1108** detect IP objects within an IP network. Gateway/NEL service **1110** provides action object processing within gateways. A

persistent repository, such as IPOP database **1112**, is updated to contain information about the discovered and monitored IP objects. Other ORB or core services **1114** may also access IPOP database **1112**.

5 Customer address manager service **1116** queries IPOP **1112** during operations that allow an administrator to resolve addressability problems. Customer logical network creator **1118** fetches administrator input about the groupings of physical networks into a logical network, as may be provided
10 by an administrator through an application GUI, such as the GUI shown in **Figure 13**. From this input, the various scopes of the physical networks are combined to create a logical scope as previously described above.

VPN creator **1120** fetches administrator input concerning
15 which physical networks belong to which customer. The administrator can provide a name to each physical network collection, which is used by the anchorname creator **1122** to define an anchorname, which is highest level name used to describe a logical network. The final name of each physical
20 network is a combination of the anchorname and the name assigned to each logical network. For example, the name of a logical network consisting of the physical networks 146.5.*.* would be "austin\downtown\secondfloor" comprising the anchorname="austin" and the name="downtown\secondfloor."
25 The anchorname creator supplies a name to the IP Driver subsystem by combining the anchorname, determined from the scope configuration, and the name of the physical network element object from IPOP. Finally, a customer ID creator **1124** uses the collection of IDs used by all customers to
30 generate a new unique customer identifier when required by IPOP; the identifiers are used rather than strings for efficient database searches of large number of network

objects. During subsequent operations to map the location of a user to an ORB, customer address manager service **1116** queries may query an active-user database similar to that shown in **Figure 6**.

5 With reference now to **Figures 11B-11D**, some simplified pseudo-code depicts the manner in which action objects and endpoint objects can be implemented in an object-oriented manner. **Figure 11B** shows a class for action objects, while **Figures 11C-11D** show classes for endpoint objects.

10 With reference now to **Figure 12A**, a flowchart depicts a portion of an initialization process in which a network management system prepares for managing a set of networks with multiple NATs. It is assumed that a network administrator has already performed configuration processes on the network such that configuration information is properly stored where necessary. The process begins when a multi-customer administrator creates DKS VPN IDs during installation (step **1202**). For example, after the ORB has started, the ORB starts a Command Line Interface (CLI) Service through which an administrator can issue CLI commands to create VPN IDs within the IPOP database, such as "ipop create VPN" used by customer and VPN ID creator **1124** in order to create a unique customer ID or a unique VPN ID.

15 The process then continues with the multi-customer administrator creating network scope for one or more customers (step **1204**). Multi-customer regions may also be created, which refers to the managing a region that consists of two or more customers for which care has to be taken not to intermix different customer data. At this point, the physical network is discovered via a discovery engine, such as the IP driver service, which performs a discovery process to identify IP objects and stored those in the IPOP

20

25

30

persistence storage. For all customer locations, all of the physical networks that have been discovered are displayed to the administrator so that the administrator can conveniently apply names to the discovered objects/networks. In addition, multiple address problems are determined and displayed to the administrator, who is then required to assign a VPN ID to a customer, e.g., by using an application GUI such as that shown in **Figure 13**.

Part of the customer scope, i.e. a logical scope consisting of a collection of physical networks as described previously, is the customer anchorname text array, e.g., "ibm\usa\Austin", the customer name, and a unique customer ID, as created by customer address manager service **1116** in **Figure 11A**. The hash number is computed by the customer base text name, e.g., "ibm", the network addresses, e.g., all subnets of reserved public addresses, and VPN IDs.

The administrator then resolves any outstanding addressability problems (step **1206**). For example, a large corporation may have subnets "10.0.0.*" on each floor of a large office. After those have been resolved, then the system stores the mapping of customers, VPN IDs, customer anchornames, and customer networks in the IPOP database (step **1208**), and the initialization process is then complete.

With reference now to **Figure 12B**, a flowchart depicts further detail of the initialization process in which the administrator resolves addressability problems. **Figure 12B** provides more detail for step **1206** shown in **Figure 12A** in which an administrator proceeds to resolving identified addressability problems.

The process begins, during the initialization process, as an ORB starts the customer address manager (step **1212**).

The customer address manager then finds the identity of the administrator that is performing various address management functions through a network management application (step **1214**). At this point, the identity of the network administrator may be used to ensure than the administrator has the proper authorization parameters. However, for the sake of explanation, it may be assumed that an administrator with multi-customer rights has access to the GUI to create VPNs for multiple customers, i.e. it may be assumed that an administrator has the proper authorization for working with the data from multiple customers. The multi-customer administrator uses the administrator GUI shown in **Figure 13**, which uses the customer address manager, to display all of the discovered networks for the administrator's customer or customers (step **1216**).

After retrieving this information, the customer address manager may then allow the administrator to assign VPN IDs to those networks for which it can be determined that the networks have an addressability problem (step **1218**). The assigned VPN IDs are then stored as updated information within the network objects within IPOP (step **1220**). The scope information is also updated with a VPN ID (step **1222**); initially, many scopes are defined as "VPN = 0", which means no VPN address. The VPN ID creator ensures that unique VPN IDs are created such that duplicate addresses can exist within a VPN that has an assigned VPN ID. This portion of the initialization process is then complete. The manner in which the administrator assigns VPN IDs is explained in more detail with respect to **Figure 12C**.

In order to determine which networks require a VPN ID, the customer address manager sorts through all of the network addresses, looking for problematic addresses. For

example, a set of 255 public addresses, such as "10.0.0.*", are reserved for local network purposes. Hence, even if two networks within the network management system do not have colliding local network addresses, the potential for future collisions exists.

With reference now to **Figure 12C**, a flowchart depicts further detail of the process in which the administrator assigns VPN IDs. **Figure 12C** provides more detail for step **1218** shown in **Figure 12B**. The process begins by displaying those networks have been determined to need a VPN ID assigned since a duplicate address exists, as determined with respect to step **1218** above, to the current administrator (step **1232**). The customer address manager then displays a list of possible VPN IDs from which the administrator may choose (step **1234**), and the administrator is able to define VPN IDs as necessary if not already defined (step **1236**). VPN IDs could have been previously defined through the configuration service, most likely during installation. However, at configuration time, the networks have not yet been discovered, so it is not possible for the system to know if and where duplicate addresses exist. While the figures are described with respect to the actions of a single administrator, a highly distributed system has a collection of administrators that are typically not in one location. Hence, one of goals of the DKS management framework is to detect errors and allow the administrators to have input into the manner in which the errors should be corrected.

A determination is then made as to whether the administrator is a multi-customer administrator (step **1238**). If not, then the VPN ID that has been chosen by the administrator can be assigned to the networks of the

administrator's customer (step **1240**). If the administrator is a multi-customer administrator, then the customer address manager must get a specific customer from the administrator (step **1242**), and the chosen VPN ID is assigned to the specified customer (step **1244**). This portion of the initialization process is then complete. After these initialization steps, the administrator has an overall addressing scheme that should be coherent. The IP addresses, VPN IDs, and other information, when taken together, provides a scheme for unique identifiers that the management system can use to manage the devices throughout the system.

With reference now to **Figure 13**, a figure depicts a graphical user interface window that may be used by a network or system administrator to set monitoring parameters for resolving address collisions. Window **1350** is a dialog box that is associated with a network management application; a system or network administrator is required to create or enter VPN IDs to resolve duplicate addresses that have been detected, such as physical network addresses **1352** and **1354**. An administrator could also invoke the application on a regular basis when necessary, or it could be invoked automatically by the network management system when address collisions are detected. "Set" button **1374** and "Clear" button **1376** allow the administrator to store the specified values or to clear the specified parameters. Checkbox **1378** allows an administrator to quickly change the VPN ID for an entire physical scope indicated within window **1350**.

Figures 14A-14B depict examples of processes that may be performed by the network management system after system configuration/initialization when an administrator is using

a network management application to perform a certain operation, such as a simple IP "Ping" command as shown in the example. While the example shows a simple IP "Ping" action, a more complex action could include a software distribution application that installs software on endpoints throughout the distributed data processing system.

With reference now to **Figure 14A**, a flowchart shows the overall process for performing an IP "Ping" within a multi-customer, distributed data processing system containing multiple private networks. The process begins when an ORB starts a private network multi-customer manager (PNMCM) that is used by the system to perform certain actions, such as requesting an IP "Ping" (step **1402**). The user of the application, which in this case is a network or system administrator for a particular customer, launches an application associated with the PNMCM (step **1404**). Within the application, the administrator chooses an endpoint and requests an IP "Ping" action, most likely from hitting a "Ping" button within the GUI (step **1406**).

The PNMCM manager attempts to fetch the requested endpoint from the IPOP database using only the IP address as specified or selected by an administrator within an application GUI (step **1408**). A determination is then made as to whether IPOP returns duplicate endpoints (step **1410**). If not, then the process branches to show the results of the requested "Ping" action.

If there is a collision among duplicate IP addresses, they are displayed to the administrator along with the previously associated VPN IDs that help to uniquely identify the endpoints (step **1412**). The administrator is requested to choose only one of the duplicate endpoints (step **1414**), and after choosing one, the administrator may request to

perform the "Ping" action on the selected endpoint (step **1416**). The PNMCM displays the results of the "Ping" action to the administrator (step **1418**), and the process is complete.

5 With respect to **Figure 14B**, a flowchart depicts a process for obtaining and using an application action object (AAO) within the network management system of the present invention. An application action object is a class of objects that extends an action object class in a manner that
10 is appropriate for a particular application. The process begins when an application requests, from the gateway service, an application action object (AAO) for a "Ping" action (AAOIP) against a target endpoint (step **1422**). The process assumes that the administrator has already
15 chosen the source and target endpoints through some type GUI within a network management application.

 The gateway service asks the NEL service to decode the target endpoint from the request (step **1424**). As noted previously, one of the primary roles of the NEL service is
20 to support the requests from applications for routes, as explained above with respect to **Figure 3**. The NEL service then asks the IPOP service to decode the endpoint object (step **1426**). Assuming that the processing has been
25 successfully accomplished, IPOP returns an appropriate AAOIP object to the NEL service, including VPN ID if necessary (step **1428**), and the NEL service returns the AAOIP object to the gateway service (step **1430**). The gateway service then returns the AAOIP object to the application (step **1432**). The application then performs the desired action (step
30 **1434**), such as an IP "Ping", and the process is complete.

 The description of **Figures 11A-14B** explain a methodology for configuring the network management framework

to manage the networks of multiple customers; by employing scopes and anchors, the logical networks can be configured and managed. As described above with respect to **Figures 5A-5C**, when a network is discovered, it is associated with a particular scope, and each scope relates to an anchor. Scope configuration is important to the proper operation of the IP drivers because IP drivers assume that there are no overlaps in the drivers' scopes. Since there should be no overlaps, every IP driver has complete control over the objects within its scope. When IP mapper is informed that a new network has been discovered, it uses the scope associated with the network to determine with which anchor, i.e. customer, the newly discovered network should be associated, and the appropriate updates are also made within the topology database.

Assuming that an administrative user has the proper security access, the administrative user should have the ability to modify various management aspects of scopes and anchors within the network management framework, although scope manipulation can be quite complex. For example, an administrative user may incorrectly attempt to change the manner in which a set of endpoints is managed such that a conflict between scopes arises. Hence, the network management framework needs to be able to display scopes properly in order for an administrative user to be able to retrieve and view the topology of the networks that are being managed.

As noted previously, in a highly distributed system comprising on the order of a million devices with many customers and administrators using a common network management framework provided by a single service provider, system displays that varied only with respect to network-related information would be inadequate. For

example, a typical network management application displays information associated with the physical or logical configurations of a set of networks, such as information pertaining to the status and type of devices or
5 communication links within the distributed system. These displays may graphically differentiate system information using various types of icons or color-coded information so that an administrative user can view portions of networks in an easy-to-understand, graphical manner. However, for a
10 large distributed system such as those intended to be managed by the network management framework disclosed herein, typical application displays would be filled with similar icons for most subnetworks, which would be rather monotonous for an administrative user, and most displays may
15 appear to be redundant.

Hence, the network management framework of the present invention provides the ability for an administrative user to enhance or customize the graphical displays of network-related information by incorporating other graphical
20 items in order to make the topology display more user-friendly. A typical network management application display of device icons can be rather tiresome. In the present invention, an administrator can add, select, or otherwise incorporate a variety of user-friendly icons and
25 digital images that depict additional types of information; these topology display enhancements are described in more detail further below.

Approaching the problem from one direction, enhancing and/or customizing the presentation of topology information
30 within a network management framework helps to alleviate the problem of information overload associated with viewing information generated by a highly distributed system comprising on the order of a million devices with many

customers and administrators using a common network management framework provided by a single service provider. Approaching the problem from a different direction, restricting and/or minimizing the presentation of topology information within a network management framework would also help to alleviate the problem of information overload.

Typically, a network management application allows an administrative user to vary the amount of detail that can be viewed with respect to the components or status of a network system, such as zooming in and out of a topology display, which would be useful but inadequate for the present invention.

In contrast, the network management framework of the present invention provides the ability for an administrative user to limit the amount of network-related information in a topology display with respect to the security access of the administrative user, with respect to the scopes that are defined within the topology, and with respect to the logical divisions of customers throughout the distributed data processing system. These topology display restrictions are described in more detail further below.

In the present invention, the network management framework can manage the physical networks of multiple customers as a conglomeration of logical networks. To this end, the network management framework uses the concept of an anchor. As explained above, an anchor is a root name in a hierarchical naming space under which the network management framework can associate networks. From a more dynamic perspective, an anchor is the foundational element with which the network management framework can associate the topology which is discovered by the network management framework. Users can define, under an anchor, scopes that belong to the same customer, to the same logical or

geographic region, or to some other logical association.

The "anchormame" is the name within a hierarchical name space with which the network management framework can associate other logical identifiers. An anchormame is the highest level (root) name used to describe a hierarchical, logical network. The final name of each physical network is a combination of the anchormame and the name assigned to each logical network. For example, the name of a logical network consisting of the physical networks in 146.5.*.* could be "austin\downtown\secondfloor" comprising the anchormame="austin" and the name="downtown\secondfloor." As shown with respect to **Figure 13**, an administrative user can supply an anchormame through an anchormame creator GUI; the supplied anchormame is provided to the IP driver subsystem, which combines the anchormame with other IPOP information to generate a unique name for each network element object within IPOP.

In addition to managing logical networks using an anchor, the network management framework of the present invention uses special container objects termed "aggregate topology objects" to manage logical networks. The basic information discovered by an IP driver is shown to an administrative user through a GUI, such as that shown in **Figure 9A**, in a tree format via the topology service. The topology service provides four types of objects. The first type of topology object is an aggregate topology object; aggregate topology objects act as containers and contain data as well as other topology objects. The second type of topology object is merely termed a "topology object"; topology objects contain data only and cannot contain other container objects, yet topology objects can exist in multiple containers. The third type of topology object is an aggregate relation, which would be presented within a GUI

as a line to depict a relationship between two objects; aggregate relations can be formed between topology objects and aggregate topology objects in order to place a topology object inside of a container. The last type of topology object is a peer relation object representing a peer relation; peer relations can be formed between topology objects that exist within the same container.

A customer may be represented within a topology map by creating an aggregate topology object for the customer's anchor. At a highest possible level, a service provider may be represented within a topology map by creating an aggregate topology object for the service provider, which then contains a plurality of customer containers.

With reference now to **Figure 15**, a flowchart depicts a process in which a newly discovered endpoint can be added to a multi-customer topology. The process shown in **Figure 15** is similar to the process shown in **Figure 8A** except that **Figure 15** provides more detail with respect to a multi-customer topology. The process begins with a new endpoint being discovered by an IP driver (step **1502**) and the IP mapper for the IP driver creates a topology object to represent the new endpoint (step **1504**).

Various aggregate relations may possibly be needed for the newly discovered endpoint. First, an aggregate relation is formed between the system in which the endpoint resides and the endpoint itself (step **1506**). If the endpoint resides in a network in which the other endpoints within the endpoint's system do not reside, then a relation needs to be created between the endpoint's system and its network (step **1508**).

A determination is then made as to whether or not the endpoint's system now resides in multiple networks

underneath the same anchor, which would necessarily also mean within the same customer, and whether the endpoint's system is a router (step **1510**). If not, then no further action is required. If so, then an aggregate relation needs to be created between the anchor object and the network (step **1512**), and peer relations are created between the networks and the system (step **1514**).

After completing the creation of the topology objects, the data must be persisted within the IPOP and topology databases, after which the process can be considered to be complete. The IP mapper writes the endpoint object to the IPOP database and to the topology database, after which the IP mapper listens for a successful write to both the IPOP database and the topology database. If both writes complete successfully, then the both writes are committed to the respective database.

With reference now to **Figures 16A-16D**, a set of flowcharts depicts a process in which the network management framework can create different types of multi-customer topology views for an administrative GUI application using the anchor container objects of the present invention. The process begins with the IP mapper requesting that the topology service create the first layer of a topology tree/map to be displayed (step **1602**). In the present invention, the first layer of a topology map would be the anchors, which would usually represent different customers; hence, the anchor objects, which are container objects, are created for holding their respective networks are placed in the appropriate anchor containers. IP mapper then requests that the topology service create network containers for holding their respective system objects (step **1604**). IP mapper subsequently requests that the topology service

create system containers for holding their respective endpoint objects (step **1606**).

After this setup process, the IP driver essentially begins listening to any containers that the topology service subsequently displays in the administrative GUI application for user input that requests some manner for viewing the topology information. Hence, the IP driver begins waiting for the user to select or activate a particular view of the topology information (step **1608**).

If the user selects to view endpoints by a specific IP driver (step **1610**), then the process branches to handle this choice. If the user selects to view information in a tree view showing everything has been discovered by all IP drivers, then the process branches to handle this choice (step **1612**). If the user selects to view the information in a three-dimensional view showing everything that has been discovered by all IP drivers, then the process branches to handle this particular choice (step **1614**). If none of these views have been chosen, then the process may be considered to be completed, although the administrative GUI application would most likely continue to cycle waiting for additional user input. Alternatively, other view choices may be available to the user.

In order to process the selection at step **1610**, the GUI application via the topology service displays a list of IP drivers and their respective scopes from which the administrative user may choose, although the list is based on whether or not the administrator has authorized security access to a particular scope or IP driver (step **1620**). The administrative user then chooses a particular IP driver from the list (step **1622**), and the topology service fetches the anchor containers that were created by this IP driver from

the topology database (step **1624**). The GUI application then displays all of the anchors associated with the selected IP driver and waits for the administrative user to choose one of the anchors (step **1626**), after which the user may select one of the anchors in order to examine more closely the topology under the selected anchor (step **1628**). When an anchor is selected, then the topology service fetches topology objects associated with this particular network, i.e. system and endpoint topology objects, and displays them (step **1630**). The user may continue exploring the topology of these objects, after which the process may be considered to be complete.

In order to process the selection at step **1612**, the GUI application via the topology service obtains a list of all IP drivers, although the list is based on whether or not the administrator has authorized security access to a particular scope or IP driver. The topology service fetches all anchor containers that were created by these IP drivers from the topology database (step **1640**). The GUI application then displays all of the anchors associated with these IP drivers and waits for the administrative user to choose one of the anchor container objects, after which the topology service then fetches the topology objects associated with this particular anchor and displays them as a tree (step **1642**). The user may continue exploring the topology of these objects, after which the process may be considered to be complete.

In order to process the selection at step **1614**, the GUI application via the topology service obtains all elements in the selected 3-D view from the topology database (step **1650**). The GUI application then displays all of the allowable elements based on whether or not the administrator

has authorized security access to a particular element (step **1652**). The 3-D tree view is displayed such that the elements are arranged as a tree, but all branches of the tree have already been expanded or extended; preferably, the depth of the elements within the tree are shown based on how far or close the endpoints are from the anchor customer in a distance relationship. The user may continue exploring the topology of these objects, after which the process may be considered to be complete.

As previously described above, the network management framework may contain a security subsystem for determining whether or not an administrative user has authorized access to a scope, logical network, etc. Because all topology objects and IPOP objects can be associated with a security context, the display of topology objects can easily be restricted within the network management framework of the present invention, as shown in **Figures 16A-16D**.

With reference now to **Figure 17**, a flowchart depicts a process in which a display of a topology tree can be enhanced with non-network-related information. As noted above, a topology display of more than a million devices could be very repetitive, no matter what view or subview of the distributed data processing system is requested by an administrative user. Given the manner in which the topology service within the network management framework employs container objects for displaying the topology of the system, the present invention takes advantage of the container objects to allow the topology display to be customized, as explained below.

The process begins with an administrative user selecting a topology object to be viewed within a network management application that is displaying a topology map

within its GUI (step **1702**). In response, the topology service requests the object from the topology database (step **1704**).

5 A determination is then made as to whether the selected object is a container object and whether the object is a customer anchor object (step **1706**). If so, then the topology service gets the customer administrator name that has been specified as being responsible for the customer's logical network that is associated with the anchor object
10 (step **1708**); the topology service can ask the IP mapper to query the IPOP database to retrieve this information. The customer administrator name is then used to retrieve the administrator's picture from the appropriate database (step **1710**), and the retrieved picture is associated with the
15 selected container object (step **1712**), and the process is complete.

If the determination is negative at step **1706**, a determination is then made as to whether the selected object is a container object and whether the object is an IP driver
20 logical network object (step **1714**). If so, then the topology service gets the administrator name that has been specified as being responsible for the selected logical network (step **1716**). The name of the IP driver's administrator is then used to retrieve the administrator's
25 picture from the appropriate database (step **1710**), and the retrieved picture is associated with the selected container object (step **1712**), and the process is complete.

If the determination is negative at step **1714**, a determination is then made as to whether the selected object
30 is a container object and whether the object is a system with an active administrative console (step **1718**). If so, then the topology service gets the administrator name that

is currently logged into the system (step **1720**); this may be obtained from a database such as active user database **606** shown in **Figure 6A**. The name of the system's administrator is then used to retrieve the administrator's picture from the appropriate database (step **1710**), and the retrieved picture is associated with the selected container object (step **1712**), and the process is complete.

The determination steps **1706**, **1714**, and **1718** are merely examples of the types of conditions that may be evaluated in an attempt to retrieve a graphic image or icon for the selected topology object. Other conditions may be configurable through the configuration service and may be based on various combinations of determinations, such as system state, available graphics, etc.

After a new graphic object is associated with the container object, the topology service then retrieves the container's graphic object for display rather than displaying a default graphic or icon. Instead of forcing the topology service to wait for a user action before setting a new graphic object for the container, the topology service may initiate the retrieval itself; for example, the topology service may consult a configuration service for a policy concerning the manner in which graphic objects should be handled by the topology service.

The examples in **Figure 17** show that a previously stored administrator picture may be used in place of a graphic icon. However, other types of graphic images could be obtained, such as flags that indicate a country location of a particular network, system, or endpoint. Moreover, real-time or near-real-time digital images could be retrieved; for example, a security camera that is directed at a system device could be shown, thereby providing a

useful security purpose through a topology map.

The advantages of the present invention should be apparent in view of the detailed description of the invention that is provided above. A network management framework flexibly manages multiple customers within a highly distributed system. The network management system allows a network administrator to vary the GUI display of topology by viewing non-network related information along with the topology of the physical and logical organizations of the networks that are being managed. In addition, the network management framework allows an administrative user to restrict the display of the topology of the networks in accordance with the security access of the user and/or in accordance with the logical divisions of the distributed data processing system with respect to multiple customers.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of instructions in a computer readable medium and a variety of other forms, regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include media such as EPROM, ROM, tape, paper, floppy disc, hard disk drive, RAM, and CD-ROMs and transmission-type media, such as digital and analog communications links.

The description of the present invention has been presented for purposes of illustration but is not intended to be exhaustive or limited to the disclosed embodiments. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiments were chosen

Variable	Mean	SD	Min	Max
Age	30.1	4.2	18	45
Gender	Male	1.2	0	2
Marital status	Married	1.5	0	2
Education	High school	1.0	0	2
Occupation	Unemployed	1.0	0	2
Income	Low	1.0	0	2
Health status	Good	1.0	0	2
Stress level	Low	1.0	0	2
Life satisfaction	Low	1.0	0	2
Depression	Low	1.0	0	2
Loneliness	Low	1.0	0	2
Self-esteem	Low	1.0	0	2
Resilience	Low	1.0	0	2
Optimism	Low	1.0	0	2
Gratitude	Low	1.0	0	2
Forgiveness	Low	1.0	0	2
Empathy	Low	1.0	0	2
Prosocial behavior	Low	1.0	0	2
Life satisfaction	Low	1.0	0	2
Depression	Low	1.0	0	2
Loneliness	Low	1.0	0	2
Self-esteem	Low	1.0	0	2
Resilience	Low	1.0	0	2
Optimism	Low	1.0	0	2
Gratitude	Low	1.0	0	2
Forgiveness	Low	1.0	0	2
Empathy	Low	1.0	0	2
Prosocial behavior	Low	1.0	0	2